

Dress



Designer Ruby™

HUSQVARNA VIKING® Sewing Machines and Accessories

- DESIGNER RUBY™ Sewing and Embroidery Machine
- Vogue pattern V2900
- Suitable fabric – Bridal Satin or Shantung
- DESIGNER RUBY™ Sampler Designs # 001 and 008
- DESIGNER™ Royal Hoop (360 x 200mm)
412 94 45- 01)
- DESIGNER™ Optional Endless Hoop (170 x100mm)
920 051-096
- Inspira Cutwork needles
- Ultra Solvy Sulky water soluble stabilizer (40403)
#140002165
- Appliqué Scissors # 412 615 501

Interfacing

To determine the right interfacing to purchase and where it goes on the garment follow the Pattern instructions.

When making tailored garments, interfacing is the key to obtaining professional results. There are many different kinds of interfacing available today, both fusible and sew-in. For best results, you should select an interfacing that is slightly lighter weight than your fashion fabric.

Tip: Follow the manufacturer's instructions for fusing the interfacing to the fabric. Holding the iron still for the recommended time will ensure a permanent bond.

Cutting:

- Cut out all the pieces for the dress with the included 5/8" (1,5cm) seam allowance.
- We added 4" (10cm) extra seam allowance on both of the center back pieces to fit all 11 embroideries.
- Bring the design into your 5D™ Embroidery Software and print paper templates of the embroidery around the hem, and for placement of all embroideries. Cut out the designs and place them on the skirt pattern, add width if necessary.

The fabulous Design Positioning feature on the DESIGNER RUBY™ sewing and embroidery machine means you can match your embroideries perfectly even after hooping the fabric. Consult your User's Guide for more information

Sewing:

- To insure a good fit, sew the dress in muslin or another similar fabric and make the changes before you start to cut and sew in the fashion fabric for the dress.

- Cut out all the pattern pieces in the fabric and overcast all edges with an overlock stitch to prevent fraying during the embroidering.
- Select the weight of fabric you are sewing on the Sewing Advisor and enter Seam to stitch the side seams of the dress.
- Sew all but one of the seams on the dress leaving the center back seam open for easy hooping and to place the fabric around the machine while embroidering. Pin the side seams together and start to sew from the hem edge. The HUSQVARNA VIKING® Exclusive Sensor System will keep the layers of fabric even.

Embroidering on satin bridal fabric

- Use an embroidery needle, size 75
- Always test your embroidery on scraps of the actual fabric with the stabilizer and threads you will be using before starting your project.
- Hoop the fabric with water soluble stabilizer underneath and if the fabric needs more support use two layers of stabilizer underneath the fabric.

Cutwork Embroidery

- Consult your DESIGNER RUBY™ Sampler for more information on cutwork needle embroideries.

Embroidering the skirt

- Start to embroider the hem of the dress. The first embroidery should be placed on the center front. The fabulous Design Positioning feature on the DESIGNER RUBY™ sewing and embroidery machine means you can match your embroideries perfectly even after hooping and re-hooping the fabric. Consult your User's Guide for more information.
- Continue with all the embroidering around the edge of the Skirt

Embroidering the waistband

- Sew the side seams of the waistband and press the seams open. Start by placing one of the embroideries on the center front of the piece. Continue embroidering all the way around the piece using the connecting stitches for perfect placement.

Sew the dress

- Use the instruction from the pattern to sew the rest of the dress. Before you sew the shoulder seams, embroider a flower (embroidery no. 008) on the left shoulder.